

# TECHNICAL DATA SHEET

## ACP line

The ACP generators are small, transportable ozone generators ideal for deodorization in closed spaces - odor and air treatment in rooms, cars and boats. The ozone is blown out through a fan.

	ACP-100	ACP-200	ACP-1000	ACP-3500	ACP-7000
Ozone concentration output*	0,1 g/h	0,2 g/h	1,0 g/h	3,5 g/h	7,0 g/h
Ozone production technique	Ceramic plate	Ceramic plate	Quartz tube	Ceramic plate	Ceramic plate
Optional capacity control	No	Optional 50/100%	Optional 0-100%	Optional 0-100%	Optional 0-100%
Capacity control	On/Off	0-100%	On/Off	On/Off	On/Off
Energy consumption	11 W	11 W	65 W	80 W	95 W
Dimensions (HxWxD)	150 x 130 x 120 mm	150 x 130 x 120 mm	330 x 160 x 130 mm	260 x 130 x 260 mm	260 x 130 x 260 mm
Weight	1,2 kg	1,2 kg	2,4 kg	3,8 kg	3,8 kg
Ozone output	Fan				
Mounting	Free standing				
External Connection	Standard: On/Off ; Optional: Safety sensor, regulator or 0-100%				
Operation condition	+5° to + 35 ° C (optim. 15° C) - <50% rH				
Supply Voltage	230 V / 50 Hz				
Cover	Stainless steel				
Warranty**	1 year limited warranty				

\*Relative to ambient conditions. All technical changes and upgrades are reserved INFUSER

\*\*See warranty conditions

ACP- 100/200



ACP- 500 / 1000



ACP- 3500 / 7000

